# Incremental encoder 900 PPR, Ø38 mm housing, Ø6 mm shaft, push-pull output

EOI-38-900-6-PP · Push-pull · IP50 · 5…26 V DC




## FEATURES

- Optical incremental encoder, Ø6 mm solid shaft, 900 PPR
- Push-pull output: A, B, Z
- Supply 5…26 V DC · max. response frequency 100 kHz
- Ø38 mm housing · IP50 · max. 6000 rpm

## WIRING

| | |
|---|---|
| **Red** | +V |
| **Black** | 0 V |
| **White** | A |
| **Green** | B |
| **Yellow** | Z |
| **Shield** | shield |

Connect the shield to ground.

## GENERAL

| | |
|---|---|
| Encoder type | Incremental, solid shaft |
| Resolution | 900 PPR |
| Output circuit | Push-pull |
| Output signals | A, B, Z |
| Max. response frequency | 100 kHz |
| Phase shift A/B | 90° ± 45° |
| Direction of rotation | A leads B clockwise (viewed from the shaft) |

## ELECTRICAL

| | |
|---|---|
| Supply voltage | 5…26 V DC |
| Current consumption (max.) | 60 mA |
| Output level (high / low) | Vdc − 2.5 V / < 1 V |
| Output current (max.) | 20 mA |
| Rise/fall time (max.) | 2 µs |
| Reverse polarity protection | Yes |
| Max. cable length | 50 m at 50 kHz |

## MECHANICAL

| | |
|---|---|
| Housing diameter (max.) | 38 mm |
| Housing diameter tolerance | 0 / −0.02 |
| Body diameter | 35 mm |
| Total length incl. shaft | 52 mm |
| Shaft diameter | 6 mm |
| Shaft diameter tolerance | 0 / −0.02 |
| Shaft length from mounting face | 17 mm |
| Shaft flat length | 10 mm |
| Centring spigot diameter | 20 mm |
| Centring spigot tolerance | 0 / −0.02 |
| Mounting hole circle (PCD) | 30 mm |
| Mounting holes | 6 × M3, depth 5 mm |
| Max. speed | 6000 rpm |
| Starting torque (max.) | 30 gf·cm |


Specifications subject to change without notice. © 2026 Mekelson Components S.L.

## MECHANICAL

| | |
|---|---|
| Max. axial shaft load | 1 kg |
| Max. radial shaft load | 2 kg |
| Weight (max.) | 200 g |
| Cable exit | Radial |
| Cable diameter | 4.5 mm |
| Cable length | 1 m |

## ENVIRONMENT

| | |
|---|---|
| Operating temperature | 0…60 °C |
| Operating humidity (non-condensing) | 35…90 % RH |
| Storage temperature | −20…70 °C |
| Protection class | IP50 |
| Vibration | 10 g, 10–55 Hz, 1.5 mm, 2 h |
| Shock | 20 g, 11 ms |

## COMPLIANCE AND QUALITY

| | |
|---|---|
| CE marking | EMC 2014/30/EU (EN 61000-6-3, EN 61000-6-1) |
| RoHS | 2011/65/EU incl. (EU) 2015/863 |
| REACH (SVHC) | < 0.1 % by weight |
| Manufacturer's quality system | ISO 9001:2015 |

## ARTICLE CODE EOI-38-900-6-PP

| | |
|---|---|
| EOI | Optical incremental encoder |
| 38 | Housing Ø38 mm · options: 38, 44, 50 |
| 900 | 900 pulses per revolution · options: 5…3600 |
| 6 | Shaft Ø6 mm · options: 6, 8 |
| PP | Push-pull · options: PP push-pull, LD line driver |

## ORDERING INFORMATION

| | |
|---|---|
| Article | EOI-38-900-6-PP |
| Series | EOI-38-6 – Encoder Ø38 mm, 6 mm shaft |
| Country of origin | Taiwan |

## OUTPUT SIGNALS




Phase shift A–B: 90° ± 45° (T/4 ± T/8). Z: one high pulse per revolution. Clockwise rotation viewed from the shaft: A leads B.

## OUTPUT CIRCUIT




Same circuit for A, B and Z. Max. output current 20 mA; output level (high / low) Vdc − 2.5 V / < 1 V. Works with PNP and NPN inputs.

## DIMENSIONS




Front view Side view

Mounting holes: 6 × M3, depth 5 mm · Radial cable Ø4.5 mm, 1 m · Dimensions in mm. Schematic drawing, not to scale.


Specifications subject to change without notice. © 2026 Mekelson Components S.L.

## RESOLUTIONS IN SERIES EOI-38-6

| PPR | Push-pull | Line driver |
|---|---|---|
| 5 | EOI-38-5-6-PP | EOI-38-5-6-LD |
| 10 | EOI-38-10-6-PP | EOI-38-10-6-LD |
| 50 | EOI-38-50-6-PP | EOI-38-50-6-LD |
| 100 | EOI-38-100-6-PP | EOI-38-100-6-LD |
| 200 | EOI-38-200-6-PP | EOI-38-200-6-LD |
| 300 | EOI-38-300-6-PP | EOI-38-300-6-LD |
| 360 | EOI-38-360-6-PP | EOI-38-360-6-LD |
| 400 | EOI-38-400-6-PP | EOI-38-400-6-LD |
| 500 | EOI-38-500-6-PP | EOI-38-500-6-LD |
| 600 | EOI-38-600-6-PP | EOI-38-600-6-LD |
| **900** | **EOI-38-900-6-PP** | **EOI-38-900-6-LD** |
| 1000 | EOI-38-1000-6-PP | EOI-38-1000-6-LD |
| 1024 | EOI-38-1024-6-PP | EOI-38-1024-6-LD |
| 1200 | EOI-38-1200-6-PP | EOI-38-1200-6-LD |
| 1500 | EOI-38-1500-6-PP | EOI-38-1500-6-LD |
| 1800 | EOI-38-1800-6-PP | EOI-38-1800-6-LD |
| 2000 | EOI-38-2000-6-PP | EOI-38-2000-6-LD |
| 2048 | EOI-38-2048-6-PP | EOI-38-2048-6-LD |
| 2500 | EOI-38-2500-6-PP | EOI-38-2500-6-LD |
| 3600 | EOI-38-3600-6-PP | EOI-38-3600-6-LD |

Other outputs on request: NPN/PNP open collector.

Other resolutions, cable lengths and connectors on request.

Download 3D model (STEP): EOI-38-6_1.step


Specifications subject to change without notice. © 2026 Mekelson Components S.L.